

Single Doors 502A-P | 512-P | 522-P

BS EN 179



TWO POINT LOCKING

Classification No.	3	7	6	B	1	3	2	2	B	A
EN 179 : 2008										

- 502A-P** Push Pad Emergency Exit Bolt For Wooden Doors
- 502A-P/AD** Push Pad Emergency Exit Bolt For Aluminium Doors
- 502A-P/UD** Push Pad Emergency Exit Bolt For uPVC Doors

The Exidor 502A-P is an elegant and highly functional emergency exit bolt for single and double door applications. Incorporated as standard is an automatic top trip. The main body is fitted with an anti-thrust device, which prevents leverage of both the top and bottom shoot bolts from their sockets.

- 512-P** Push Pad Emergency Exit Bolt With Vertical Latches For Wooden Doors
- 512-P/AD** Push Pad Emergency Exit Bolt With Vertical Latches For Aluminium Doors
- 512-P/UD** Push Pad Emergency Exit Bolt With Vertical Latches For uPVC Doors

The Exidor 512-P offers all the elegance and functions of the Exidor push pad emergency exit bolt with the added feature of vertical Pullman latches which increases security and offers a smooth latching action.

- 522-P** Push Pad Emergency Exit Bolt With Horizontal Latches For Wooden Doors
- 522-P/AD** Push Pad Emergency Exit Bolt With Horizontal Latches For Aluminium Doors
- 522-P/UD** Push Pad Emergency Exit Bolt With Horizontal Latches For uPVC Doors

The Exidor 522-P offers all the elegance and functions of the Exidor push pad emergency exit bolt with the added feature of horizontal Pullman latches which increases security and offers a smooth latching action.

- Non-handed
- CE marked for safety
- Surface mounted
- 38mm wide footprint
- Suitable for doors with narrow stiles
- Standard colours: silver, white with green push pad and black with red push pad
- Available in most RAL colours




Standard Sizes

Standard size emergency exit bolts are suitable for single doors up to 2440mm high. Special sizes are available on request.

Optional accessories for all the single emergency exit bolts

- 500/LEC Outside access device with Euro cylinder – lever operated
- 500/LEA Outside access device with Euro aperture – lever operated
- 500/KEC Outside access device with Euro cylinder – knob operated
- 500/KEA Outside access device with Euro aperture – knob operated
- CL1 Mechanical push button outside access device
- CL2 Mechanical push button outside access device with passage facility
- CL3 Quick code mechanical push button outside access device
- CL4 Quick code mechanical push button outside access device with passage facility

Exidor threshold seal ES1 can be fitted as an alternative to the floor keep. Please suffix CB after the product code i.e. 502A-P/CB (See Exidor door seal range leaflet for details)



502A-P

512-P

522-P