



CONSTRUCTION PRODUCTS REGULATION 2011
DECLARATION OF PERFORMANCE

DoP Number: **DoP_EEC-0004-01**

Issue: 3

- 1. Unique identification code of the product-type:**
3470 Electro-Hydraulic Hold Open Floor Spring.
- 2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) of the CPR:**
3470.
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**
For use on fire and smoke compartment doors.
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**

EXIDOR LIMITED, PROGRESS DRIVE, CANNOCK, STAFFS, WS11 0JE, UK
- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**
N/A
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**
System 1
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**
Standard: EN1155: 1997 + A1: 2002
Notified certification body No.1121.
Certificate of Constancy of Performance: 1121-CPD-AE0004
- 8. European Technical Assessment :**
N/A

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Ability to Release		EN 1155:1997:A1:2002
5.1.2 Release from any angle	Pass	
5.1.3 Not possible to inhibit the release	Pass	
5.1.4 Supply voltage	Pass	
5.1.5 External electrical connection	Pass	
5.1.6 Inlet for external wiring	Pass	
5.2.1 General		
5.2.2 Electrical release	Pass	
5.2.3 Door closing device EN1154 requirements	(see separate DoP 2950 range)	
5.2.4 Durability	25,000 Electrical 25,000 Mechanical	
5.2.5 Angle of hold	>65°	
5.2.6 Manual release	>40 Nm but <120 Nm	
5.2.7 Continues hold open	Pass	
5.2.8 Overload performance	Pass	
5.2.9 Delayed release	Pass	
5.2.10 Electrical performance	Pass	
5.2.11 Temperature rise	Pass	
5.2.12 Damage	Pass	
5.2.13 Fire/smoke doors	Grade 1	
	Pass	
Durability of Self Closing.		
5.2.14.1 Corrosion	Grade 3 (96 Hours)	
5.2.14.2 Corrosion	Pass	
Control of Dangerous substances		
Annex ZA3	PASS	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'R. Darby', is written over a faint horizontal line.

Robin Darby – Technical Manager
Date of Issue: 03/02/2016

Exidor Limited
Progress Drive
Cannock
Staffordshire
WS11 0JE
United Kingdom